

EPF-HP 3311

METALWORKING FLUID FOR HIGH PRESSURE MACHINES

Description

EPF-HP 3311 is a neo-synthetic metalworking fluid designed for high pressure coolant applications. The product is found in systems with pistons and positive displacement pumps that increase coolant pressure up to 2000 psi.

EPF-HP 3311 has a sulfonate free emulsifier package that provides exceptional stability even in high pressure systems. The product is often found displacing low foaming synthetic formulations.

The product provides “soluble-oil” performance with sump stability that approaches that of a synthetic product. The product is non-irritating to workers’ skin and will not cause dermatitis issues.

EPF-HP 3311 provides excellent rust protection due to a proprietary manufactured tri-phase corrosion inhibitor package.

Features & Benefits

- Designed for high pressure machining systems
- Low to no foam
- Extended tool life with increased production rates
- Best in class resistance to bacteria growth
- Exceptional tramp oil rejection
- Outstanding surface finish
- Non-irritating to operators’ skin

Health & Safety

See the most recent MSDS which is available directly from Precision Fluids, your local salesman, or authorized distributor. Precision Fluids uses only raw materials not listed as carcinogenic by IRAC.

Physical Data

Appearance:	Translucent Green
Diluted Appearance:	Milky Light Green
Solubility	Water
Odor:	Mild Industrial
Specific Gravity:	0.97
Concentrate pH:	9.3
pH, 5 % dilution:	9.0
Freeze/Thaw Cycles:	Passed 3x

Application & Usage

Precision Fluids recommends using our Super Green cleaner before adding EPF-HP 3311 to a machine.

The recommended concentration for EPF-HP 3311 is 10% for optimum results. However, results for any operation can only be determined through testing.

Maintaining the coolant at its optimum concentration is achieved through daily refractive index checking.

No special precautions are necessary with respect to seals or valves.

Refractive Index Monitoring (1.1X multiplier)

Percent	Ratio	Refractometer Reading
5	19 to 1	4.6
10	9 to 1	9.1
15	6 to 1	13.7
20	4 to 1	18.3

Precision Fluids • 5230 Brittmoore Road • Houston, TX 77041
Phone: 713-896-0606 • Fax: 713-896-0610 • www.precisionfluids.com