

WAYLUBES

SLIDEWAY OILS FOR INDUSTRIAL APPLICATIONS

Description

Waylubes are designed specifically for the lubrication of machine tool slideways and similar applications where an adhesive or tacky lubricant is required. Special lubricity additives provide minimal machine tool way chattering and stick-slip, resulting in smoother more accurate machining.

Additionally, Waylubes improve tool operation and provide fewer work piece rejects. These oils are also recommended for the lubrication of chains, lo-speed bearings, gears, and other applications where tacky oil is beneficial in reducing leakage.

Applications

Waylubes are fully approved by Cincinnati Milacron under their P-47 and P-50 specifications.

Health & Safety

See the most recent MSDS which is available directly from Precision Fluids, your local salesman, or authorized distributor. Precision Fluids uses only raw materials not listed as carcinogenic by IRAC.

Properties

Product Name	Waylube Way Oil 32	Waylube Way Oil 68	Waylube Way Oil 220
Viscosity @ 40°C, cSt	31	66	220
Viscosity @ 100°C, cSt	5.2	8.4	19.0
Viscosity @ 100°F, SUS	160	342	1105
Viscosity @ 210°F, SUS	44	55	98
Viscosity Index	97	97	95
Flash Point, °F	400	445	505
Pour Point, °F	-27	-25	5
Gravity, API	32.6	30.9	28
Copper Corrosion	1a	1a	1a
Stick Slip Adhesive	Yes	Yes	Yes

Precision Fluids • 5230 Brittmoore Road • Houston, TX 77041
Phone: 713-896-0606 • Fax: 713-896-0610 • www.precisionfluids.com